

FEATURERS



Fast pull down

Better cooling performance



Coil evaporator

Better temperature uniformity



Inner-door design

5 individual inner door




Universal castor wheels

Proven heavy-duty castors with brake



Lockable doors

Standard locks with keys



MDF-25V328E Pull Down Test at Ambient



High-quality steel materials

Antibacterial and corrosion resistant



Precise temp. control

Temp. control accurate to 0.1°C



5 types of alarm

Audible and visual alarms




Variable space

Height adjustable shelves



Eco-friendly

CFC-free refrigerant and energy-saving





STRUCTURE





Sensor erro alarm

High/low temp. alarm

Power failure alarm

Door ajar alarm

Thermostat failure alarm



Coil evaporator cooling system makes the chamber temperature more uniform.

The 4 independent inner doors give the cabinet better insulation performance and are more convenient to use.

PARAMETER

Performance		Refrigeration System		Alarms	
Cooling method	Direct Cooling	Refrigerant	R290	High/low	Υ
Defrost	Manual	Temp. controller	Microprocessor	Power failure	Υ
Shelf/drawer	Shelves/4	Sensor	NTC	Sensor error	Υ
Temperature range	-10℃~-25℃	Display	Digital display	Controller failure	Υ
Ambient temperature	10~32℃	External material	SPCC sprayed steel	Door ajar	Υ
Noise (db)	46	Compressor QTY	1	Power failure backup	8 hours

Electrical Data		Dimensions		Other	
Voltage frequency(V/Hz) 220V 50Hz/60Hz		Package size(W*D*H)(mm)	770*770*2040	Inner door Qty	5
Power (W)	218W	Capacity (L/cu.ft)	328/11.6	Remote alarm port	Optional
Current (A)	1.59A	Exterior size(W*D*H)(mm)	673*676*1886	Access port QTY/Dia.	1/25mm
Power consumption	1.7 kWh/24h	Interior size(W*D*H)(mm)	508*455*1393	Internal material	SPCC sprayed steel

