### -40°C MEDICAL DEEP FREEZER





## **FEATURERS**



### Fast pull down

Better cooling performance



#### **Coil evaporator**

Better temperature uniformity



## Inner-door design

4 individual inner door




#### **Universal castor wheels**

Proven heavy-duty lockable castors



#### **Lockable doors**

Standard locks with keys



MDF-40V268E Pull Down Test at Ambient



### **High-quality steel materials**

Antibacterial and corrosion resistant



#### Precise temp. control

Temp. control accurate to 0.1°C



### 5 types of alarm

Audible and visual alarms




### Variable space


Height adjustable shelves



#### **Eco-friendly**


CFC-free refrigerant and energy-saving





# **STRUCTURE**







Coil evaporator cooling system makes the chamber temperature more uniform.

The 4 independent inner doors give the cabinet better insulation performance and are more

# **PARAMETER**

Performance		Refrigeration System		Alarms	
Cooling method	Direct Cooling	Refrigerant	R290	High/low temperature	Υ
Defrost	Manual	Temp. controller	Microprocessor	Power failure	Υ
Shelf/drawer	Shelves/3	Sensor	NTC	Sensor error	Υ
Temperature range	-20℃~-40℃	Display	Digital display	Controller failure	Υ
Ambient temperature	<b>10~32</b> ℃	External material	SPCC sprayed steel	Door ajar	Υ
Noise (db)	48	Compressor QTY	CUBIGEL/1	Power failure backup	8 hours

Electrical Data		Dimensions		Other	
Voltage frequency( V/Hz	2) 220V 50Hz/110V 60Hz	Package size(W*D*H)(mm)	770*770*1804	Inner door	4
Power (W)	309W	Capacity (L/cu.ft)	268/9.46	Remote alarm port	Optional
Current (A)	1.5A	Exterior size(W*D*H)(mm)	673*676*1630	Access port QTY/Dia.	1/25mm
Power consumption	5.2 kWh/24h	Interior size(W*D*H)(mm)	508*455*1137	Internal material	SPCC sprayed steel

